

## Show Caps

Made by Leea Customs

Caps are designed to fit snug and can just be pressed onto the matching cap. In the case of the power steering, oil and brake, if you find the cap a tight fit. You may find it easier to remove the OEM cap, place the cap cover on a soft cloth and press the oem cap into the cover making sure to align the graphics as you like. The washer cap is a complete replacement, so remove the OEM washer cap prior to install. The washer cap will snap over the bottle and may feel loose once installed, but will be secure. To attach the caps in a more permanent fashion you can apply the provided VHB tape disks. They must be applied only to a surface that is above 60 degrees and very clean. Clean the tops of each cap using the provided alcohol wipe. Dry with a clean paper towel and repeat using a new wipe and a new clean towel. **Apply the VHB disk to the tops of each OEM cap** (the small disc is for the clutch cap if your car is equipped). Press evenly and then remove the top liner. Position the custom cap facing in the desired position and press down to seat the cap, you will not be able to reposition once the cap is seated. Do not try to remove for 24hrs as the VHB gains full strength. Use a good quality chrome polish or wax to care for your caps.

All installation and use of the products purchased from Nakidparts.com / LEEA Customs Inc. are done at the owners own risk. Nakidparts can not be held responsible for any damage or injury caused by the installation or use of the products purchased here (sorry, the lawyers made me say it)

The user agrees to these terms by the act of using / purchasing these products